## DUTCH BOY -- ALKYD WOOD STAINS, 875 OAK -- 8010-00N019549

Product ID:ALKYD WOOD STAINS, 875 OAK MSDS Date:06/01/1988 FSC:8010 NIIN:00N019549 MSDS Number: BLCWF === Responsible Party === Company Name: DUTCH BOY Box:6709 City:CLEVELAND State:OH ZIP:44101 Country:US Info Phone Num:216-566-2902 Emergency Phone Num:216-566-2917 CAGE:85231 === Contractor Identification === Company Name: DUTCH BOY Box:6709 City:CLEVELAND State:OH ZIP:44101 Country:US Phone:216-566-2902 CAGE: 59019 Company Name: DUTCH BOY Box:6709 City:CLEVELAND State:OH ZIP:44101 Country:US Phone: 216-566-2902 CAGE:85231 Ingred Name:MINERAL SPIRITS, VP:2 CAS:64742-47-8 Fraction by Wt: 75% OSHA PEL:500 PPM (MFR) ACGIH TLV:100 PPM (MFR) Ingred Name: MINERAL SPIRITS; (MINERAL SPIRITS 140-FLASH), VP:0.5 CAS:64742-88-7 Fraction by Wt: 10% ACGIH TLV:100 PPM (MFR) Ingred Name:TOLUENE (SARA III) CAS:108-88-3 RTECS #:XS5250000 Fraction by Wt: <5% OSHA PEL:200 PPM/150 STEL ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Ingred Name: SUPP DATA: BLDGS & OTHER COMBUSTIBLE MATERIALS. RTECS #:9999992Z Ingred Name: OTHER PREC: NOT IN USE. TRANSFER ONLY TO APPRVD CNTNRS W/COMPLETE & APPROP LABELING. DO NOT TAKE INTERNALLY. KEEP (ING 6)

Ingred Name: ING 5: OUT OF REACH OF CHILDREN. INTENT MISUSE BY DELIB CONC & INHALING CONTENTS CAN BE HARMFUL/FATAL. RTECS #:9999992Z Ingred Name: RESP PROT: WHICH MAY BE GENERATED FROM PROD, UNDERLYING PAINT/ABRASIVE. RTECS #:9999992Z Ingred Name: VENT: 1910.94, 1910.107, 1910.108. RTECS #:9999992Z LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: ACUTE: IRRIT OF EYES/SKIN/RESP SYS. MAY CAUSE NERV SYS DEPRESS. EXTREME OVEREXP MAY RESULT IN INCON & POSS DEATH. HDCH/ DIZZ/NAUS/LOSS OF COORD ARE INDICATIONS OF EXCESSIVE EXPOS TO VAPS/SPRAY MISTS. R EDNESS & ITCHING/BURNING SENSATION MAY INDICATE EYE/EXCESSIVE SKIN EXPOS. CHRONIC: PRLNG OVEREXP TO SOLV (EFTS OF OVEREXP Explanation of Carcinogenicity:NOT RELEVANT. Effects of Overexposure: HLTH HAZ: INGRED LISTED IN SECT II MAY CAUSE ADVERSE EFTS IN LIVER/URINARY/BLOOD FORMING & CVS. RPTS HAVE ASSOC RPTD & PRLNG OVEREXP TO SOLV W/PERMANENT BRAIN & NERV SYS DMG. Medical Cond Aggravated by Exposure: NONE GENERALLY RECOGNIZED. First Aid: INHAL: REMOVE FROM EXPOS. RESTORE BRTHG. KEEP WARM & OUIET. SKIN:WASH AFFECTED AREA THORO W/SOAP & WATER. REMOVE CONTAM CLTHG & LAUNDER BEFORE REUSE. EYES:FLUSH W/LARGE AMTS OF WATER FOR AT LEAST 15 MI N. GET MD. INGEST: NEVER GIVE ANYTHING BY MOUTH TO UNCON PERSON. DO NOT INDUCE VOMIT. GIVE SEVERAL GLASSES OF WATER. GET MD. Flash Point Method: PMCC Flash Point:95.0F,35.0C Lower Limits:0.9% Extinguishing Media:CO2, DRY CHEMICAL, FOAM. Fire Fighting Procedures:WEAR NIOSH/MSHA APPRVD SCBA & FULL PROT EQUIP . H20 SPRAY MAY BE INEFTIVE. IF H20 IS USED, FOG NOZZ ARE PREF. H20 MAY BE USED TO COOL CNTNRS TO (SUPDAT) Unusual Fire/Explosion Hazard: KEEP CNTNRS TIGHTLY CLSD. ISOLATE FROM HEAT/ ELEC EQUIP/SPKS/OPEN FLAME. CLSD CNTNRS MAY EXPLODE WHEN EXPOS TO EXTREME HEAT. APPLICATN TO HOT SURFS REOS (SUPDAT Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. VENTILATE & REMOVE W/INERT ABSORBENT. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER. Handling and Storage Precautions: USE ONLY W/ADEQ VENT. AVOID BRTHG VAP/SPRAY MIST & CNTCT W/SKIN/EYES. CONTENTS ARE FLAMM. KEEP AWAY FROM HEAT/SPKS/OPEN FLAME. CONSULT NFPA CODE.

RTECS #:9999992Z

Other Precautions: DURING USE & UNTIL ALL VAPS ARE GONE: KEEP AREA VENTED, DO NOT SMOKE, EXTING ALL FLAMES/PILOT LIGHTS/HEATERS, TURN OFF STOVES/ELEC TOOLS/APPLIANCES/ANY OTHER SOURCES OF IGNIT. USE APPRVD BONDING & GROU NDING PROC. KEEP CNTNR CLSD WHEN (ING 5) ======= Exposure Controls/Personal Protection ========== Respiratory Protection: IF PERS EXPOS CANNOT BE CONTROLLED BELOW APPLIC LIMS BY VENT, WEAR NIOSH/MSHA APPRVD PROPERLY FITTED ORG VAP/PARTICULATE RESP FOR PROT AGAINST MATL. WHEN SANDING/ABRADING DRIED FILM, WEAR NIOSH/ MSHA APPRVD DUST/MIST RESP FOR DUST (ING 7) Ventilation:LOC EXHST PREF. GEN EXHST ACCEPTABLE IF EXPOS TO MATLS IS MAINT BELOW APPLIC EXPOS LIMS. REFER TO OSHA STDS (INGRED 8) Protective Gloves: IMPERVIOUS GLOVES . Eye Protection: CHEMICAL WORKERS GOGGLES . Other Protective Equipment: NONE SPECIFIED BY MANUFACTURER. Work Hygienic Practices: WASH HANDS AFTER USING. Supplemental Safety and Health FIRE FIGHT PROC: PRVT PRESS BUILD-UP & POSS AUTOIGNIT/EXPLO WHEN EXPOS TO EXTREME HEAT. EXPLO HAZ: SPECIAL PREC. DURING EMER CNDTNS OVEREXP TO DECOMP PRODS MAY CAUSE HLTH HAZ. SYMP MAY NOT BE IMMED APPA RENT. GET MD. TO AVOID SPONT COMBUSTION, SOAK OILY CLOTHS IN H20 AFT USE/PLACE IN CLSD METAL CNTNR AWAY FROM (ING 4) HCC:F4 Boiling Pt:B.P. Text:222F,106C Vapor Pres:SEE INGRED Vapor Density:>AIR Evaporation Rate & Reference: SLOWER THAN ETHER. Appearance and Odor:COLOR - OAK Percent Volatiles by Volume:85 Stability Indicator/Materials to Avoid:YES NONE SPECIFIED BY MANUFACTURER. Stability Condition to Avoid: NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Products: BY FIRE: CO & CO2. Waste Disposal Methods: WASTE FROM PROD MAY BE HAZ AS DEFINED UNDER RCRA 40 DFR 261. WASTE MUST BE TESTED FOR IGNITABILITY TO DETERMINE APPLIC EPA HAZ WASTE NUMBERS. INCIN IN APPRVD FACILITY. DO NOT INCIN CLSD CNTNR. DISP OF I/A/W FED, STATE & LOC REG REGARDING POLLUTION. Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.