PPG INDUSTRIES -- BOBCAT ENAMEL REDUCER, DTE201 -- 8010-00F006641

Product ID: BOBCAT ENAMEL REDUCER, DTE201 MSDS Date: 01/01/1987 FSC:8010 NIIN:00F006641 MSDS Number: BBWDJ === Responsible Party === Company Name: PPG INDUSTRIES/CLEVELAND, OH 44111 Emergency Phone Num: (304) 843-1300 CAGE: EO498 === Contractor Identification === Company Name: PPG INDUSTRIES INC Address:4325 ROSANNA DR Box:City:ALLISON PARK State: PA ZIP:15101 Country: US Phone: 412-492-5555 CAGE:88373 Company Name: PPG INDUSTRIES/CLEVELAND, OH 44111 CAGE: EO498 ====== Composition/Information on Ingredients ======== Ingred Name:TOLUENE (SARA III) CAS:108-88-3 RTECS #:XS5250000 Fraction by Wt: 50% OSHA PEL:200 PPM/150 STEL ACGIH TLV:50 PPM; 9293 EPA Rpt Otv:1000 LBS DOT Rpt Qty:1000 LBS Ingred Name: ALIPHATIC HYDROCARBON Fraction by Wt: 15% ACGIH TLV:100 PPM Ingred Name: NAPHTHA (PETROLEUM SPIRITS OR BENZIN) CAS:8030-30-6 RTECS #:SE7555000 Fraction by Wt: 15% OSHA PEL:100 PPM Ingred Name: AROMATIC HYDROCARBON, LIGHT AROMATIC NAPHTHA Fraction by Wt: 20% ======= Hazards Identification =========== Effects of Overexposure: SKIN, EYE & RESP TRACT IRRIT/CNS

DEPRESSION/HEADACHE/DIZZINESS/STAGGERING GAIT/CONFUSION OR COMA.

First Aid:INHALATION: REMOVE FROM EXPOSURE. RESTORE BREATHING. NOTIFY PHYSICIAN. EYES: FLUSH WITH WATER FOR AT LEAST 15 MINUTES. TAKE TO PHYSICIAN FOR DEFINITIVE MEDICAL TREATMENT. SKIN: WASH WITH WATER. REMOVE CONTAMINATED CLOTHING. CONSULT PHYSICIAN.

======================================
File Fighting Measures
Flash Point: 23F PMCC
Lower Limits: 1.1%
Extinguishing Media:CO2, DRY CHEMICAL OR FOAM Fire Fighting Procedures:WATER SPRAY MAY BE INEFFECTIVE. FOG NOZZLES ARE PREFERABLE.
Unusual Fire/Explosion Hazard: WATER TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP & POSSIBLE AUTOIGNITION OR EXPLOSION.
========== Accidental Release Measures ==========
Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION (FLAMES, HOT SURFACES & ELECTRICAL, STATIC OR FRICTIOL SPARKS). AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE WITH INERT ABSBENT & NON-SPARKING TOOLS.
======================================
Handling and Storage Precautions:DON'T STORE >120F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED & PROTECTED FOR STORAGE OF NFPCLASS IB FLAMMABLE LIQUIDS. DON'T TAKE INTERNALLY. Other Precautions:INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING & INHALING CONTENTS CAN BE HARMFUL OR FATAL. DON'T FLAME CUT, BRAZE OR WELDITHOUT NIOSH APPROVED RESPIRATORS OR APPROPRIATE VENTILATION.
======= Exposure Controls/Personal Protection ========
Respiratory Protection: OPEN AREAS: FILTER RESPIRATORS FOR OVERSPRAY. Ventilation: PROVIDE LOCAL EXHAUST VENTILATION TO KEEP AIR Evaporation Rate & Reference: SLOWER THAN ETHER Percent Volatiles by Volume: 100.
========== Stability and Reactivity Data ==========
Stability Indicator/Materials to Avoid:YES Hazardous Decomposition Products:FUMES MAY CONTAIN: CO
======== Disposal Considerations ===========
Waste Disposal Methods: DISPOSE IN ACCORDANCE WITH LOCAL, STATE &

FEDERAL REGULATIONS. DON'T INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.