

PROS CHOICE Pro Mound (#4006051)

(312)321-1515, Information (800)424-9300, Emergency

PRODUCT IDENTIFICATION

MSDS Number: 4006051

Identity: PROS CHOICE Pro Mound

Issued: January 22, 2007

Chemical Name: Montmorillonite Clay

Component CAS Number Amount Feldspar 68476-25-5 10-20% Bulk Smectite 12199-37-0 >50% Bulk Quartz (crystalline silica) .00065% in the respirable range 14808-60-7 10-30% Bulk

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This product is a non-combustible, chemically inert mineral. This mineral sample contains a small amount of naturally-occurring crystalline silica as quartz. Prolonged overexposure to respirable crystalline silica may cause lung disease (silicosis). IARC, in Monograph 68, has concluded that crystalline silica inhaled in the form of quartz from occupational sources is carcinogenic to humans (Group 1); however, carcinogenicity was not detected in all industrial circumstances studied. Because applications and exposure data indicate that exposure to respirable quartz in this product with normal use is well below the OSHA Permissible Exposure Limit (PEL) and ACGIH Threshold Limit Value (TLV); and because the company is not aware of any scientific or medical data available indicating that exposure to dust from this product under conditions of normal use will cause silicosis or cancer; adverse effects would not be expected from normal use of this product.

HEALTH HAZARDS

INGESTION: No adverse effects expected with unused material.

INHALATION: Inhalation of excessive concentrations of dust may cause irritation of mucous

membranes and upper respiratory tract.

EYE: Contact may cause mechanical irritation and possible injury.

SKIN: No adverse effects expected.
SENSITIZATION: No adverse effects expected.

CHRONIC/CARCINOGENICITY:

Inhalation of excessive concentrations of any dust, including this material, may lead to lung injury. This product contains crystalline silica. Excessive inhalation of respirable crystalline silica may cause silicosis, a progressive, disabling and fatal disease of the lung. Symptoms may include cough, shortness of breath, wheezing and reduced pulmonary function. The International Agency for Research on Cancer (IARC), in Monograph 68 has concluded that crystalline silica inhaled in the form of quartz or cristobalite, from occupational sources is carcinogenic to humans (Group 1). However, in making the overall evaluation, the Working Group noted that carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on

Issued on January 22, 2007 Page 1 of 5



PROS CHOICE Pro Mound (#4006051)

(312)321-1515, Information (800)424-9300, Emergency

inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs. The National Toxicology Program (NTP) classifies crystalline silica as a known carcinogen. Because applications and exposure data indicate that exposure to respirable quartz in this product with normal use is well below the OSHA Permissible Exposure Limit (PEL) and ACGIH Threshold Limit Value (TLV); and because the company is not aware of any scientific or medical data available indicating that exposure to dust from this product under conditions of normal use will cause silicosis or cancer; adverse effects would not be expected from normal use of this product.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

None currently known.

4. FIRST AID MEASURES

EYE: Immediately

Immediately flush eyes with cool running water, lifting upper and lower lids. If irritation

persists or for foreign body in the eye, get immediate medical attention.

SKIN:

None needed for normal use.

INGESTION:

If used material is ingested, get medical attention due to possibility of chemical

contamination. If large amount of unused material is swallowed, get immediate medical

attention.

INHALATION:

Remove to fresh air.

5. FIREFIGHTING MEASURES

FLASH POINT:

This product is not combustible.

FLAMMABLE LIMITS Not applicable

EXTINGUISHING MEDIA:

Use media that is appropriate for surrounding fire.

UNUSUAL FIRE OR EXPLOSION HAZARDS:

None

SPECIAL FIREFIGHTING INSTRUCTIONS

None required.

HAZARDOUS COMBUSTION PRODUCTS:

None

6. ACCIDENTAL RELEASE MEASURES

Sweep up and collect for re-use or disposal

7. HANDLING AND STORAGE

HANDLING:

Avoid breathing dust. If clothing becomes dusty, launder before re-use.

STORAGE:

Store in a dry area.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Issued on January 22, 2007 Page 2 of 5



PROS CHOICE Pro Mound (#4006051)

(312)321-1515, Information (800)424-9300, Emergency

EXPOSURE GUIDELINES:

Component

Exposure Limit

PEL - 5mg/m3 TWA
(respirable fraction)

Smectite

PEL - 5mg/m3 TWA
(respirable fraction)

PEL - 5mg/m3 TWA
(respirable fraction)

PEL - 10mg/m3/%SiO2+2 TWA
TLV - 0.025mg/m3 TWA

PEL- OSHA Permissable Exposure Limit. TLV- American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit

PEL- OSHA Permissable Exposure Limit. TLV- American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value. TWA- 8 hour Weighted Average. STEL-Short Term Exposure Limit.

ENGINEERING CONTROLS:

For operations where the exposure limit may be exceeded, local exhaust ventilation is recommended.

RESPIRATORY PROTECTION:

For operations where the exposure limit may be exceeded, a NIOSH/MSHA approved

high efficiency particulate respirator is recommended.

SKIN PROTECTION: None required for normal use.

EYE PROTECTION: Safety glasses or goggles recommended.

OTHER: None required for normal use.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR:

Dark brown to dark gray/black lumps, no odor

PHYSICAL STATE: Solid

BOILING POINT: Not applicable
VAPOR PRESSURE: Not applicable
VAPOR DENSITY: Not applicable

SOLUBILITY IN WATER:

Insoluble

SPECIFIC GRAVITY: 2.2

pH: Not applicable
MELTING POINT: Not applicable
OCTANOL/WATER COEFFICIENT:

Not available

10. STABILITY AND REACTIVITY

STABILITY:

Stable

INCOMPATIBILITY: Contact of dry clay with turpentine, vegetable oil or other unsaturated organic

Issued on January 22, 2007 Page 3 of 5



PROS CHOICE Pro Mound (#4006051)

(312)321-1515, Information (800)424-9300, Emergency

compounds, or with hydrofluoric acid may generate heat and/or fire. Do not use with these compounds.

HAZARDOUS DECOMPOSITION PRODUCTS:

None

HAZARDOUS POLYMERIZATION:

Will not occur.

11. TOXICOLOGICAL INFORMATION

No data available.

12. ECOLOGICAL INFORMATION

No data available.

13. DISPOSAL CONSIDERATIONS

Dispose in accordance with local, state and federal environmental regulations. Unused material is suitable for disposal in sanitary landfill. Used material may be subject to regulation, depending on the nature of the material absorbed. Check with appropriate regulatory authority for used material containing hazardous waste.

14. TRANSPORT INFORMATION

PROPER SHIPPING NAME:

Not regulated

UN NUMBER:

Not applicable

HAZARD CLASS/PACKING GROUP:

Not applicable

LABELS REQUIRED: None

15. REGULATORY INFORMATION

CERCLA/SUPERFUND None

SARA HAZARD CATEGORY (311/312):

Chronic Health

SARA 313:

None

TSCA:

All of the components of this product are listed on the EPA TSCA Inventory or exempt

from notification requirements.

EINECS:

All of the components of this product are listed on the EINECS Inventory or exempt

from notification requirements

EEC R&S Phrases:

Not Classified as Dangerous under EEC Labeling Regulations

JAPAN MITI:

All of the components of this product are existing chemical substances as defined in the

Chemical Substances Control Law.

AICS:

All of the components of this product are listed on the AICS Inventory or exempt from

notification requirements

Issued on January 22, 2007 Page 4 of 5



PROS CHOICE Pro Mound (#4006051)

(312)321-1515, Information (800)424-9300, Emergency

CANADIAN DSL:

All of the components of this product are listed on the Canadian Domestic Substance

List or exempt from notification requirements.

CA PROPOSITION 65: This product contains respirable crystalline silica which is known to the State of

California to cause cancer.

16. OTHER INFORMATION

NFPA RATING:

Health=1 Fire=0 Reactivity=0

HMIS RATING:

Health=1* Fire=0 Reactivity=0

The information in this data sheet is believed to be accurate. However, each purchaser should make its own test to determine the suitability of the product for its purposes. OIL-DRI CORPORATION OF AMERICA MAKES NO WARRANTY, EXPRESSED OR IMPLIED, WITH RESPECT TO THE PRODUCT and assumes no responsibility for any risk or liability arising from the use of the information or the product. Statements about the product should not be construed as recommendations to use the product in infringement of any patent.

Issued on January 22, 2007 Page 5 of 5